

## ■ LCL 系列铝电解电容器

### LCL Series Aluminum Electrolytic Capacitor

#### ◆特征 Features

\*长寿命、高可靠性: 105℃ 5000 小时

Longer life and High reliability: 105℃ 5000 hours.

\* 耐大纹波电流

High ripple current

\* 符合 RoHS

Compliant to the RoHS Directive




#### ◆应用 Application

\*适用于光伏逆变器、高级开关电源、电源设备、变频器等其他高可靠电子产品

Ideally suited for solar inverter, high professional, switch mode power supplies, power supply unit, frequency converters and other electronic products.

#### ◆型号表示法 Part Number

8		222		VA		M		A060		CL		N		0		1		1		0			
代码 Code		产品类别 Type		代码 Code		电压 Voltage		代码 Code		尺寸 Dimensions ΦDxL(mm)		代码 Code		商标 Trademark		代码 Code		内码 Internal Code		代码 Code		产品脚型 Lead Forming Type	
8		成品 Product		MB		160		2225		Φ22x25		N		LH.NOVA		1		105℃		0		散装品 Bulk	
				MC		200		A025		Φ35x25						2		125℃					
				MD		250		A060		Φ35x60						8		85℃					
				MF		350		H065		Φ40x65													
				VA		400																	
代码 Code		标称容量 Nominal Capacitance		代码 Code		误差 Tolerance		代码 Code		型号 Series		代码 Code		胶管颜色 Sleeve Color		代码 Code		内码 Internal Code					
820		82uF		K		±10%		CL		LCL		0		黑色 Black		1		正常品					
222		2200uF		V		± <sup>20</sup> <sub>10</sub> %						1		深蓝色 Deep-blue		7		长焊针品					
332		3300uF		M		±20%						9		棕色 Brown		F		短焊针品					
														绿色 Green									

**◆产品结构 Product Structure**

**◆主要特性表 Main specifications**

项目 Item	主要特性 Performance Characteristics			
额定工作电压范围 Rated Voltage Range	160~550V.DC			
使用温度范围 Operating Temperature Range	160~350V.DC：-40℃~+105℃ 400~550V.DC：-25℃~+105℃			
标称静电容量范围 Nominal Capacitance Range	82~3300μF			
静电容量允许偏差 Capacitance Tolerance	±20% (M, +20℃, 120Hz)			
漏电流 Leakage Current (20℃)				
	额定工作电压(V) Rated working voltage	160~550		
	漏电流 Leakage current	5 分钟后 $I\leq 3\sqrt{CV}(\mu A)$ After 5 min. $I\leq 3\sqrt{CV}(\mu A)$		
	C：标称静电容量 (μF) Nominal Capacitance in μF V：额定工作电压 (V) Rated working voltage in V			
损耗角正切 DF Dissipation Factor				
	额定工作电压(V) Rated working voltage	160~420	450~500	550
	DF(MAX) (20℃,120Hz)	0.15	0.20	0.25

浪涌电压 Surge Voltage	<p>施加表中所示浪涌电压，充电 30± 5 秒，放电 5.5± 0.5 分钟作为一个周期，共进行 1000 次。温度：15℃-35℃。然后在标准大气条件下放置达到热稳定，测试各参数。 Application of DC surge Voltage stated at table,1000 times of charging for 30 ± 5 sec., discharging with a period of 5.5± 0.5 min. Test temperature: 15℃ -35℃. And the capacitor shall be stored under standard atmospheric conditions to obtain thermal stability, after which measurements shall be made.</p> <table><tr><td>额定工作电压(V) Rated working voltage</td><td>160</td><td>200</td><td>250</td><td>350</td><td>400</td><td>420</td><td>450</td><td>500</td><td>550</td></tr><tr><td>浪涌电压(V) Surge voltage</td><td>200</td><td>250</td><td>300</td><td>400</td><td>450</td><td>470</td><td>500</td><td>550</td><td>600</td></tr></table> <p>容量变化：在初始值的± 20%以内。损耗角正切值不大于规定值的 200%。漏电流：不大于初始规定值 Capacitance change: Within ± 20% of the initial value Dissipation factor: Not more than 200% of the specified value. Leakage current: more than the initial specified value.</p>	额定工作电压(V) Rated working voltage	160	200	250	350	400	420	450	500	550	浪涌电压(V) Surge voltage	200	250	300	400	450	470	500	550	600						
额定工作电压(V) Rated working voltage	160	200	250	350	400	420	450	500	550																		
浪涌电压(V) Surge voltage	200	250	300	400	450	470	500	550	600																		
高低温特性 Characteristic at high and low temperature	<p>电容器根据下表的次序处理 The capacitor shall be subjected in turn to the procedures specified below.</p> <table><tr><td>阶段 Step</td><td>温度 Temperature</td><td>时间 Time</td></tr><tr><td>1</td><td>20±2℃</td><td>热平衡状态</td></tr><tr><td>2</td><td>-40(-25)℃</td><td>*2 hours</td></tr><tr><td>3</td><td>20±2℃</td><td>热平衡状态</td></tr><tr><td>4</td><td>105℃</td><td>*2 hours</td></tr><tr><td>5</td><td>20±2℃</td><td>热平衡状态</td></tr></table> <p>* 电容器放置在每一温度下，待阻抗或电容量稳定后方可测试。 * The capacitor should be stored at each temperature until measured impedance or capacitance are stabilized .</p> <table><tr><td>阶段 2 Step 2</td><td>阻抗比（对阶段 2） Impedance ratio</td><td>见阻抗特性 refer to Impedance Stability</td></tr><tr><td rowspan="2">阶段 4 Step 4</td><td>静电容量变化率（对阶段 4） Change in capacitance</td><td>-20~+20% within -20~+20% of step 1</td></tr><tr><td>漏电流 Leakage Current</td><td>规定值 5 倍以下 Less than 500% of the specified value</td></tr></table> <p>阶段 1：测定容量、损耗和阻抗值。 Step 1: Capacitance, Dissipation Factor and impedance shall be measured. 阶段 2：放置 2 小时后，达到热平衡状态再测。 Step 2: After the capacitor being stored for 2 hours, Capacitance, Dissipation Factor and impedance shall be Measured. The measurement shall be made at thermal stability. 阶段 4：放置 2 小时后，达到热平衡状态再测。 Step 4: After the capacitor being stored for 2 hours, Capacitance, Dissipation Factor and impedance shall be Measured. The measurement shall be made at thermal stability.</p>	阶段 Step	温度 Temperature	时间 Time	1	20±2℃	热平衡状态	2	-40(-25)℃	*2 hours	3	20±2℃	热平衡状态	4	105℃	*2 hours	5	20±2℃	热平衡状态	阶段 2 Step 2	阻抗比（对阶段 2） Impedance ratio	见阻抗特性 refer to Impedance Stability	阶段 4 Step 4	静电容量变化率（对阶段 4） Change in capacitance	-20~+20% within -20~+20% of step 1	漏电流 Leakage Current	规定值 5 倍以下 Less than 500% of the specified value
阶段 Step	温度 Temperature	时间 Time																									
1	20±2℃	热平衡状态																									
2	-40(-25)℃	*2 hours																									
3	20±2℃	热平衡状态																									
4	105℃	*2 hours																									
5	20±2℃	热平衡状态																									
阶段 2 Step 2	阻抗比（对阶段 2） Impedance ratio	见阻抗特性 refer to Impedance Stability																									
阶段 4 Step 4	静电容量变化率（对阶段 4） Change in capacitance	-20~+20% within -20~+20% of step 1																									
	漏电流 Leakage Current	规定值 5 倍以下 Less than 500% of the specified value																									

阻抗特性 Impedance Stability	额定工作电压(V) Rated working voltage		160~250	315~420	450-550								
	阻抗比(120Hz)	z-25℃/z+20℃	4	7	10								
	Impedance Ratio	z-40℃/z+20℃	8	12	-								
高温负荷特性 Load life	<p>在 105±2℃环境中施加额定工作电压和最大允许纹波电流 5000 小时后,在标准大气条件下放置 16 小时后测试, 然后测试参数电容器的性能符合下面要求:</p> <p>After application of rated working voltage with max permissible ripple current specified at +105±2℃for 5000 hours, It shall be subjected to standard atmospheric for 16 hours, after which measurement shall be made.</p> <p>1、电容量变化率:±20%初始测量值以内 Capacitance change : ±20% initial measured value</p> <p>2、漏电流: ≤初始规定值 Leakage current: ≤initial specified value</p> <p>3、损耗角正切值≤200%初始规定值 Dissipation factor: ≤200% initial specified value</p> <p>4.外观: (1) 无可见损伤和无电解质漏出 No remarkable damage and electrolyte leakage (2) 底部允许轻微鼓起 Bottom allowed slightlyplumped</p> <table><tr><td>壳号 Size</td><td>判定基准 Criterion</td></tr><tr><td>&lt; φ 25</td><td>≤1.0mm</td></tr><tr><td>φ 25~30</td><td>≤1.5mm</td></tr><tr><td>≥ φ 35</td><td>≤2.0mm</td></tr></table>					壳号 Size	判定基准 Criterion	< φ 25	≤1.0mm	φ 25~30	≤1.5mm	≥ φ 35	≤2.0mm
壳号 Size	判定基准 Criterion												
< φ 25	≤1.0mm												
φ 25~30	≤1.5mm												
≥ φ 35	≤2.0mm												
高温贮存特性 Shelf life	<p>在 105±2℃环境无负荷放置 1000 小时后, 根据JIS-C-5101-4, 加额定电压30min,常温放置 24~48 后测试, 电容器的性能符合下面要求:</p> <p>After leaving capacitors under no load at +105℃for 1000 hours, According to JIS-C-5101-4, apply the rated DC voltage for 30 minutes and store the capacitors under room temperature for 24-48 hours. The capacitors meet the characteristics listed as below:</p> <p>1、电容量变化率:±20%初始测量值以内 Capacitance change : ±20% initial measured value</p> <p>2、漏电流: ≤200%初始规定值 Leakage current:≤200% initial specified value</p> <p>3、损耗角正切值≤200%初始规定值 Dissipation factor: ≤200% initial specified value</p>												
稳态湿热 Resistance to damp heat	<p>试验温湿度: 40±2℃, 90~95%RH 试验时间: 500±8h 试验后, 电容器在标准大气条件下 2 小时, 然后测试参数 Test temperature and humidity: 40±2℃, 90~95%RH Test time : 500±8h</p> <p>After completion of test, the capacitor shall be subjected to standard atmospheric conditions for 2 hours, after which measurements shall be made.</p> <p>外观: 无异状 Appearance: No remarkable abnormality</p>												

	<p>容量变化：在初始值±10%范围内  Variation of capacitance: Within ±10% of the initial value.</p> <p>损耗角正切值：不大于规定值  Dissipation factor: ≤specified value</p> <p>漏电流：不大于规定值  Leakage current: ≤specified value</p>
耐焊接热 Resistance to soldering heat	<p>焊槽法：  焊锡温度：260±5℃；浸入时间：10±1 秒；浸入深度：1.6mm  Solder bath method  Solder bath temperature : 260±5℃  Immersion time : 10±1sec.  Immersion depth: 1.6mm</p> <p>外观：无异状  Appearance: No remarkable abnormality</p> <p>容量变化：在初始值±10%范围内  Variation of capacitance: Within ±10% of the initial value.</p> <p>损耗角正切值：不大于规定值  Dissipation factor: ≤specified value</p> <p>漏电流：不大于规定值  Leakage current: ≤specified value</p>
防爆试验 Safety vent	<p>在电容器两极施加反向直流电压，其中通过的电流为：≤φ 22 逆向电流 1A, &gt; φ 22 逆向电流 10A。  Apply a reverse DC voltage to the two poles of the capacitor, where the current passing through is: ≤φ 22 Inverse current 1A, &gt; φ 22 Inverse current 10A</p> <p>如果防爆阀 30 分钟内动作，则认为产品合格。当防爆阀动作时，电容器应无打火、击穿、燃烧等现象。  If the vent does operate within 30 minutes, the test is considered to be passed. When the vent operated, the capacitor shall not flame although gas discharge or expulsion of a part of the inside element is allowable.</p>
低温放置 Low-temperature storage test	<p>在-40±2℃（160V~350V）或-25±2℃（400V~550V）环境下无负荷贮存 16h，至少恢复 16 小时,试验后检查外观，测量电容器的性能。  The capacitors are stored with no voltage applied at a temperature of -25±2℃（400V~550V）or -40±2℃（160V~350V）for 16 hours. Then it resumed 16 hours and measurements shall be made.</p> <p>外观：无异状  Appearance: No remarkable abnormality</p> <p>容量变化：在初始值±10%范围内  Variation of capacitance: Within ±10% of the initial value.</p> <p>损耗角正切值：不大于规定值</p>

	Dissipation factor: $\leq$ specified value 漏电流: 不大于规定值 Leakage current: $\leq$ specified value
耐溶剂性 Resisting Solvent	溶剂: 异丙醇 温度: 20°C~25°C; 时间: 30±5S Solvent: Isopropyl alcohol Temperature: 20°C~25°C Time: 30±5S  外观: 无异状 Appearance: No remarkable abnormality
端子强度 Terminal strength	端子抗拉强度: 沿电容器端子引出方向慢慢施加 20N 拉力 10±1 秒钟。 Tensile strength of terminal: A tensile force of 20N shall be applied to the terminals in the axial direction and acting in a direction away from the body for 10±1 sec. 端子抗弯强度: 在端子承受力最弱处(距端子引出方向 1.6mm 处), 沿垂直方向逐渐施加 25N 拉力, 并保持 30±5 秒钟然后用力一次性将端子扳回到原位。 Apply tensile force of 25N on terminals in the weakest direction gradually, after reached to the specified tensile force, keep it for 30±5 sec. Apply tensile force in the opposite direction with the same way. Carry out this operation once.  外观: 无可见机械损伤 Appearance: no visible mechanical damage 电容器应无接触不良开路或短路 The capacitor shall be no intermittent contacts, or open or short circuiting
振动试验 Resistance to vibration	在 3 个互相垂直的方向分别施加 2 小时振动, 共 6 小时。 频率: 10-55Hz 振幅峰-峰值: 1.5mm. 振速: 1 分钟内振速 10~55~10Hz Direction and duration of vibration: 3 orthogonal directions mutually each for 2h, Total 6h. Vibration frequency range: 10-55Hz. Peak to peak amplitude: 1.5mm Sweep rate: 10 to 55 to 10Hz in about 1 min.  外观: 无可见机械损伤 Appearance: no visible mechanical damage 电容器应无接触不良开路或短路 The capacitor shall be no intermittent contacts, or open or short circuiting

可焊性 Solderability	焊锡温度: $245 \pm 5^{\circ}\text{C}$ 浸入时间: $2 \pm 0.5$ 秒 Temperature of solder: $245 \pm 5^{\circ}\text{C}$ Dipping time: $2 \pm 0.5\text{sec.}$ This specification shall be met after the capacitors are stored under standard atmospheric conditions for 6 months.
	浸入焊锡的引线面积约 90% 以上应附着新锡。 At least 90% of circumferential surface of the dipping portion of terminal shall be covered with new solder.

### ◆尺寸表、允许纹波电流、纹波电流频率因子

#### Dimensions and ripple current and frequency coefficient

##### \*纹波电流频率因子

##### Ripple current frequency coefficient

频率 Frequency(Hz)		50(60)	120	300	1K	10K	> 50K
系数 Factor	160~250WV	0.80	1.00	1.17	1.32	1.45	1.50
	315~550WV	0.80	1.00	1.16	1.30	1.41	1.43

##### \*温度因子

##### Temperature Coefficients

温度 Temperature ( $^{\circ}\text{C}$ )	+40	+55	+70	+85	+105
系数 Factor	3.0	2.8	2.5	2.0	1.0

##### \*尺寸表与允许纹波电流

##### Dimensions and ripple current

Rated voltage	Rated capacitance	Case size	Rated ripple current
额定电压(V)	标称容量( $\mu\text{F}$ )	尺寸 D $\times$ L(mm)	额定纹波电流
			(A rms/ $105^{\circ}\text{C}/120\text{Hz}$ )
160	470	22 $\times$ 25	1.72
	560	22 $\times$ 30	1.95
	680	22 $\times$ 30	2.18
	680	25 $\times$ 25	2.07
	820	22 $\times$ 30	2.41
	820	25 $\times$ 35	2.41
	1000	22 $\times$ 40	2.76
	1000	30 $\times$ 25	2.87
	1200	25 $\times$ 40	3.22
	1200	35 $\times$ 25	3.22
	1500	25 $\times$ 45	3.56
	1500	30 $\times$ 35	3.68
	1800	25 $\times$ 50	4.14
	1800	22 $\times$ 40	4.02

Rated voltage	Rated capacitance	Case size	Rated ripple current
额定电压(V)	标称容量(μF)	尺寸 D×L(mm)	额定纹波电流
			(A rms/105°C/120Hz)
	2200	30×45	4.71
	2200	35×40	4.60
	2700	35×40	5.29
	2700	35×45	5.52
	3300	35×50	5.94
200	390	22×25	1.49
	470	22×30	1.72
	560	22×35	1.95
	560	25×25	1.84
	680	22×40	2.18
	680	30×25	2.20
	820	22×45	2.53
	820	25×35	2.60
	1000	25×40	2.87
	1000	35×30	3.10
	1200	25×45	3.15
	1200	35×30	3.45
	1500	30×40	3.79
	1500	35×35	3.91
	1800	30×50	4.25
	1800	25×45	4.37
	2200	35×45	4.94
	2200	35×50	5.00
	2700	35×50	5.38
250	270	22×25	1.26
	330	22×30	1.49
	390	22×35	1.61
	390	25×25	1.62
	470	22×40	1.84
	470	25×30	1.85
	560	22×45	2.07
	560	30×25	2.12
	680	25×40	2.53
	680	35×25	2.53
	820	25×45	2.64
	820	35×30	2.87
	1000	35×40	3.10
	1200	30×45	3.45
	1200	35×35	3.68




Rated voltage	Rated capacitance	Case size	Rated ripple current
额定电压(V)	标称容量(μF)	尺寸 D×L(mm)	额定纹波电流
			(A rms/105°C/120Hz)
	1500	35×45	4.14
	1500	35×55	4.37
	1800	35×50	4.60
315	180	22×25	1.15
	220	22×30	1.26
	270	22×35	1.38
	270	25×25	1.38
	330	22×40	1.61
	390	22×45	1.84
	390	25×35	1.89
	470	25×40	2.07
	470	35×25	2.10
	560	25×50	2.30
	560	35×30	2.35
	680	30×40	2.53
	680	35×35	2.60
	820	30×50	2.87
	820	35×35	2.99
	820	30×45	3.33
	820	35×45	3.36
	820	35×50	3.42
	1200	35×50	3.46
	1200	35×55	3.62
	1800	35×60	4.97
350	120	22×25	0.80
	150	22×30	0.92
	180	22×35	1.03
	220	22×40	1.15
	220	30×25	1.21
	270	22×45	1.49
	270	30×30	1.52
	330	22×50	1.61
	330	30×30	1.65
	390	25×40	1.84
	390	30×35	1.90
	470	25×45	2.07
	470	35×35	2.10
	560	30×45	2.30
	560	35×35	2.35

Rated voltage	Rated capacitance	Case size	Rated ripple current
额定电压(V)	标称容量(μF)	尺寸 D×L(mm)	额定纹波电流
			(A rms/105°C/120Hz)
	680	30×50	2.76
	680	35×40	2.80
	820	35×45	2.91
	820	35×50	2.99
	1000	35×50	3.22
400	150	22×30	1.03
	150	25×25	1.10
	180	22×35	1.15
	180	25×25	1.20
	220	22×40	1.26
	220	30×25	1.38
	270	22×50	1.49
	270	30×30	1.50
	330	35×40	1.72
	390	25×45	1.84
	390	35×30	1.95
	470	30×45	2.07
	470	35×35	2.18
	560	30×50	2.41
	680	30×65	2.64
	680	35×45	2.76
	680	35×60	2.80
	820	35×50	3.10
	1000	35×55	3.36
	1000	35×60	3.68
410	940	35×55	3.13
420	100	22×25	0.80
	120	22×30	0.92
	120	25×25	0.92
	150	30×35	1.03
	180	22×40	1.15
	180	30×25	1.26
	220	22×45	1.38
	220	30×25	1.40
	270	25×40	1.49
	270	35×25	1.72
	330	25×50	1.74
	330	35×30	1.84
	390	30×40	1.95

Rated voltage	Rated capacitance	Case size	Rated ripple current
额定电压(V)	标称容量(μF)	尺寸 D×L(mm)	额定纹波电流
			(A rms/105°C/120Hz)
	390	35×35	2.00
	470	30×50	2.18
	470	35×40	2.30
	560	35×40	2.46
	680	35×50	2.74
	820	35×55	3.30
	1000	35×65	3.74
	1200	35×75	3.99
450	82	22×25	0.74
	100	22×30	0.80
	120	22×35	0.92
	120	25×30	1.03
	150	25×35	1.26
	150	30×25	1.30
	150	30×35	1.40
	180	25×40	1.38
	180	30×30	1.40
	220	25×40	1.38
	220	30×30	1.40
	270	25×45	1.49
	270	30×35	1.48
	270	35×30	1.61
	330	30×40	1.72
	390	30×45	1.77
	390	35×35	1.74
	390	35×50	1.92
	470	30×45	1.92
	470	35×40	2.00
	470	35×50	2.20
	560	35×50	2.42
	680	35×50	2.60
	680	35×55	2.73
	820	35×60	3.04
	820	35×65	3.15
	1000	35×60	3.08
	1000	35×75	3.40
	1000	40×65	3.57
500	100	25×30	0.92
	120	25×35	1.09

Rated voltage	Rated capacitance	Case size	Rated ripple current
额定电压(V)	标称容量(μF)	尺寸 D×L(mm)	额定纹波电流
			(A rms/105°C/120Hz)
	150	30×30	1.15
	180	30×30	1.18
	180	30×35	1.26
	220	35×35	1.32
	270	25×50	1.48
	270	30×50	1.64
	330	30×50	1.68
	330	35×45	1.76
	390	35×50	1.89
	470	35×50	2.00
	470	35×55	2.10
	470	35×60	2.16
	560	35×60	2.31
	680	35×70	2.40
	680	40×60	2.52
525	120	22×40	1.07
550	82	22×35	0.78
	100	25×35	0.80
	120	25×35	1.03
	120	30×30	1.07
	150	25×40	1.09
	150	30×35	1.15
	180	35×40	1.26
	220	35×45	1.38
	270	35×50	1.49
	330	35×55	1.61
	390	35×60	1.84
	470	35×60	2.07
	680	35×80	2.54

### ◆ 产品特征曲线 Product Characteristic Curve



### ◆ 包装 Packaging

产品尺寸	纸盒	隔条	数量只/盒	外箱	盒/箱	数量/箱
Φ22*25-30	D25-43:0BZD2543-H6H	F204:0BZF204-H8H	108	B-8	10	1080
Φ22*35-40	D25-53:0BZD2553-H6H	F205:0BZF205-H8H		B-8	8	864
Φ22*45-50	D25-63:0BZD2563-H6H	F206:0BZF206-H8H		B-9	6	648
Φ25*25-30	D25-43:0BZD2543-H6H	F204:0BZF204-H8H	88	B-8	10	880
Φ25*35-40	D25-53:0BZD2553-H6H	F205:0BZF205-H8H		B-8	8	704
Φ25*45-50	D25-63:0BZD2563-H6H	F206:0BZF206-H8H		B-9	6	528
Φ25*55-60	D25-76:0BZD2576-H6H	F207:0BZF207-H8H		B-8	6	528
Φ25*65-70	D25-83:0BZD2583-H6H	F208:0BZF208-H8H		B-9	4	352
Φ25*75-80	D25-93:0BZD2593-H6H	F209:0BZF209-H8H		B-9	4	352
Φ25*85-90	D25-03:0BZD2503-H6H	F210:0BZF210-H8H		B-8	4	352
Φ30*25-30	D35-43:0BZD3543-H6H	F214:0BZF214-H8H	63	B-6	10	630
Φ30*35-40	D35-53:0BZD3553-H6H	F215:0BZF215-H8H		B-6	8	504
Φ30*45-50	D35-63:0BZD3563-H6H	F216:0BZF216-H8H		B-7	6	378
Φ30*55-60	D35-76:0BZD3576-H6H	F217:0BZF217-H8H		B-6	6	378
Φ30*65-70	D35-83:0BZD3583-H6H	F218:0BZF218-H8H		B-7	4	252
Φ30*75-80	D35-93:0BZD3593-H6H	F219:0BZF219-H8H		B-7	4	252
Φ30*85-90	D35-03:0BZD3503-H6H	F220:0BZF220-H8H		B-6	4	252
Φ35*25-30	D35-43:0BZD3543-H6H	F214:0BZF214-H8H	48	B-6	10	480
Φ35*35-40	D35-53:0BZD3553-H6H	F215:0BZF215-H8H		B-6	8	384
Φ35*45-50	D35-63:0BZD3563-H6H	F216:0BZF216-H8H		B-7	6	288
Φ35*55-60	D35-76:0BZD3576-H6H	F217:0BZF217-H8H		B-6	6	288
Φ35*65-70	D35-83:0BZD3583-H6H	F218:0BZF218-H8H		B-7	4	192
Φ35*75-80	D35-93:0BZD3593-H6H	F219:0BZF219-H8H		B-7	4	192
Φ35*85-90	D35-03:0BZD3503-H6H	F220:0BZF220-H8H		B-6	4	192

珍珠棉包装:

尺寸	每托/只	每箱/只	外箱	备注
Φ40X50	40	160	B-4	
Φ40X60	40	160	B-4	
Φ40X80	40	120	B-4	
Φ40X90	40	120	B-4	

### ◆贮存方法 Storage Methods

- \* 请保管在室温 5℃~35℃，湿度 75%RH 以下的环境
- \* (1) 产品储存期限: ≤12 个月; Storage life: ≤12 months
- \* (2) 产品储存期限超 12 个月时，需充电后再使用
- \* (3) 产品储存时间超过 3 年的应报废处理
- \* (4) 库存有效期以套管上印刷的时间开始计算
- \* (5) 请尽量以包装状态保管
- \* (6) 当电容器长期储存后，漏电流会升高，温度越高，漏电流上升越快，因此应注意储存环境。如铝电解电容器的漏电流上升对电路有不良影响，请在使用前充电处理
- \* (7) 请避免在以下环境中保管
  - ① 溅水、高温高湿及结露的环境;
  - ② 溅油、或者充满气体油成分的环境;
  - ③ 充满酸性有毒气体（硫化氢、亚硫酸、亚硝酸、氯、溴、溴化甲烷等）的环境;

\*We recommend the following conditions for storage: Ambient temperature: 5℃~35℃, Ambient humidity: Less than 75% RH.

- \* (1) Storage life: ≤12 months;
- \* (2) If storage life time is over 12 months, the products need to be recharged;
- \* (3) If storage life time is over three years, the product need to be discarded;
- \* (4) Expiry date: calculating from the date marked on the sleeve;
- \* (5) Please keep capacitors in the original package;
- \* (6) Leakage current tends to increase when capacitors have been stored for long period of time. The higher temperature , the higher leakage current increase. Please take caution when selecting the storage location. The leakage decrease gradually as voltage is applied to the capacitor. The capacitor is subjected to aging before using, leakage may cause problems in the circuit.
- \* (7) Avoid storing the capacitors under such circumstances:
  - ① Environment of water splashing, high temperature, high humidity and dewing;
  - ② The environment that splashes oil, or is filled with gas oil;
  - ③ With full of acid toxic gases environment such as( hydrogen sulfide , sulfurous acid, nitrous acid, chlorine , bromine, methyl bromide, etc.

## ◆铝电解电容器使用注意事项

### Important information on the application of aluminum electrolytic capacitors

\* (1) 直流铝电解电容器应按正确的极性使用

当直流铝电解电容器被反极性接入电路时,电容器会导致电子线路短路,由此产生的电流会引致电容器损坏。若电路中有可能在负引线施加正极电压,请选用无极性产品

\* (2) 在额定工作电压以下作用

当电容器上所施加电压高于额定工作电压时,电容器的漏电流将上升,其电气特性将在短时间内劣化直至损坏。请注意电压峰值勿超出额定工作电压

\* (3) 常规产品禁止作快速充放电使用

当常规电容器被用作快速充电用途。其使用寿命可能会因为容量下降,温度急剧上升等而缩减。

\* (4) 施加纹波电流应小于额定值

施加纹波电流超过额定值后,会导致电容器体过热,容量下降,寿命缩短。所施加纹波电压的峰值应小于额定工作电压。

\* (5) 使用环境温度

铝电解电容器的使用寿命会受到环境温度的影响。据科学统计,使用环境温度下降 10°C 其使用寿命增加 1 倍。

\* (6) 引出线强度

当拉力施加到电容器引出线,该拉力将作用于电容器内部,这将导致电容器内部短路,开路或漏电流上升。在电容器焊装到电路板,请勿强烈摇动电容器。

\* (7) 焊接过程耐热性

铝电解电容器装至电路板进行浸焊或波峰焊时,其塑料套管可能因焊接时间过长、温度过高而发生破裂或二次收缩。

\* (8) 电路板的安装孔距及安装位置

电路板安装孔的设计应与产品说明书的引线脚距相一致,如果将电容器强行插入孔距不配套的电路板,那么会有应力作用于引出线,这将导致短路或漏电流上升。

\* (9) 铝电解电容可能会有残留电压,请在使用前对电容器进行放电。

(1) When reverse voltage is applied on DC electrolytic capacitor, the capacitor will become short-circuited please use non-polarized capacitors in the circuit or the capacitor will be damage due to abnormal current flows through the capacitors since the circuit where the positive voltage may be applied to the cathode terminal.

(2) When capacitor is used at higher voltage than the rated voltage, leakage current increases, characteristics drastically deteriorate and damage in a short period may occur as a result. Please take extra caution that the peak voltage should not exceed the rated voltage.

(3) When aluminum electrolytic capacitors for general purpose are employed in rapid charge and discharge application, its life may be shorted by capacitance decreasing, heat rising, etc.

(4) Increased leakage current is common in aluminum capacitors which have been stored for long period of time. The Higher the storage temperature, the higher the leakage current increase, therefore please take precautions concerning the storage location. The leakage current decreases gradually as voltage is applied to the capacitor. In cases where increased leakage current causes problems in the circuit, apply voltage (aging) before using.

(5) Excessive heat will reduce capacitance and result in shortened life of capacitor if ripple currents exceeding the specified rated value are applied. The peak value of the ripple voltage should be less than the rated voltage.

- (6) Its ambient temperature closely affects the life of an aluminum electrolytic capacitor. It is generally stated, that life doubles for each 10°C decrease in temperature.
- (7) When a strong force is applied to the lead wires or terminals, stress is put on the internal connections. This may result in short circuit, open circuit or increased leakage current. It is not advisable to bend or handle a capacitor after it has been soldered to the PCB board.
- (8) Installation pitch-row and installation position of circuit boards  
 PCB board must be designed so its hole coincides with the lead pitch (lead spacing) of the capacitor specified by the catalog or specifications. When a capacitor is forcibly inserted into an unmatched hole, a stress is put on the leads. This could result in a short circuit or increased leakage current.
- (9) Aluminum electrolytic capacitors may have residual voltage, please discharge the capacitor before use.

### ◆推荐安装/焊接方法 Recommended Installation/Welding Methods

\*波峰焊接条件


预热: 105°C

波峰焊: 260±5°C 10±1 秒以下 (或 380±10°C 3±0.5 秒以下: 手焊)

\*Wave Soldering Conditions

Preheating: 105°C

Wave Soldering: 260±5°C for ≤10±1 seconds (or 380±10°C for ≤3±0.5 seconds for manual soldering)



### ◆其它说明 Others

\*本产品不含铅、镉等元素

This product does not include Plumbum or Cadmium.



[illegible]

Note: The content provided above is the product specification. Fenghua reserves the right to modify this content without prior notice when the product remains unchanged. Any product changes will be notified to customers via PCN.