

■车规AD系列超低阻厚膜片式固定电阻

Low Ohmic Thick Film Chip Fixed Resistor

Automotive Grade-AD



◆特征 Features

- * 符合 AEC-Q200 汽车标准相关条款
- * 适应再流焊与波峰焊
- * 电性能稳定，可靠性高
- * 具有良好的抗硫化能力
- * 符合 RoHS 指令要求
- * 符合无卤素要求
- * 潮敏等级：MSL1
- Compliant with AEC-Q200 standard
- Suit for reflow and wave flow solder
- Stable electrical capability, high reliability
- With good sulfuration-resistant performance
- Compliant with RoHS directive
- Halogen free requirement
- MSL Class: MSL1

◆应用领域 Application

- * 汽车信息系统、车载导航系统、影音娱乐系统、发动机动力控制系统、车身电子控制系统。

Automotive information system, Vehicle navigation system, Audio-visual entertainment system, Engine power control system, Electronic body control system, etc.

◆型号表示法 Part Number

AD	F	06	M	R047	F	T	13								
产品代号 Product Code	额定功率代号 Rated Power Code		型号代号 TypeCode	电阻温度系数代号 T.C.RCode	电阻值代号 Resistance ValueCode	电阻值误差 精度代号 Resistance Tolerance Code	包装方式代号 Packaging StyleCode	卷盘方式代号 ReelStyle Code							
车规AD系列超低阻厚膜片式固定电阻器 Low Ohmic Thick Film Chip Fixed Resistor Automotive Grade-AD	代号 Code	额定功率 Rated Power	代号 Code	型号 Type	三位数：前两位表示有效数字，第三位表示有效数字后零的个数。 Three digits: The first two digits are significant figures and the third one denotes number of zeros. 四位数：前三位表示有效数字，第四位表示有效数字后零的个数。 Four digits: The first three digits are significant figures and the fourth one denotes number of zeros. 小数点用 R 表示。Decimal point should be Expressed by "R". 例如Example: R005=0.005Ω R100=0.100ΩR047=0.047Ω6 M50=6.50mΩ0603: V22=22mΩ R10=0.1Ω 5M1=5.1mΩ	代号 Code	误差精度 Tolerance	代号 Code	包装方法 Packaging Style	代号 Code	卷盘方法 Reel Style				
	C	1/16W	02	0402		F	±1%	T	编带包装 Tape & Reel	空位 Blank	7英寸卷盘 7inch Reel				
	D	1/10W	03	0603		H	±3%								
	E	1/8W	05	0805											
	Y	1/6W	06	1206											
	Q	1/5W	1210	1210											
	F	1/4W	10	2010											
	R	1/3W	12	2512											
	G	1/2W	0508	0508											
	H	3/4W	0612	0612											
	J	1W	0612	0612											
	L	2W	1225	1225											
	N	3W				J	±5%				13英寸卷盘 13inch Reel				



注：1、不同厂家的超低阻产品其工艺及技术参数可能会略有差异，建议客户索样评估使用的可行性；不同厂家的超低阻产品不建议直接替换使用，我司不承担因直接替换使用而带来的经济损失。

The process and technical parameters of ultra-low resistance products from different manufactures maybe slightly different, so it is suggested that customers ask for samples to evaluate the feasibility of use; the ultra-low resistance products from different manufactures are not recommended to be replaced directly, and our company will not bear the economic losses caused by the direct replacement.

2、阻值≤50mΩ的超低阻产品，如果必须选用厚膜超低阻产品，选型时请联系原厂。For the resistance value ≤ 50mΩ, if thick film ultra-low resistance products must be selected, please contact our customer service team for selection.



◆产品结构 Construction

$R \geq 100m\Omega$ 采用正面贴装结构 Positive surface mounted structure



- ① 陶瓷基板 Ceramic Substrate
- ② 背电极 Bottom Electrode
- ③ 面电极 Top Electrode
- ④ 电阻体 Resistor Layer
- ⑤ 一次保护 Primary Overcoat
- ⑥ 二次保护 Secondary Overcoat
- ⑦ 端电极 Edge Electrode
- ⑧ 中间电极 Barrier Layer
- ⑨ 外部电极 External Electrode

$R < 100m\Omega$ 采用反面贴装结构 Reverse surface mounted structure




- ① 陶瓷基板 Ceramic Substrate
- ② 面电极 Top Electrode
- ③ 背电极 Bottom Electrode
- ④ 电阻体 Resistor Layer
- ⑤ 一次保护 Primary Overcoat
- ⑥ 二次保护 Secondary Overcoat
- ⑦ 端电极 Edge Electrode
- ⑧ 中间电极 Barrier Layer
- ⑨ 外部电极 External Electrode

◆规格尺寸 Dimensions

型号 Type	尺寸 Dimensions(mm)							
	L	W	t	a	b	*c	*d	
0402	1.00±0.05	0.50±0.05	0.30±0.05	0.20±0.10	0.25±0.10	/	/	/
0603	1.60±0.10	0.80±0.10	0.45±0.10	0.30 ±0.20	0.30 ±0.20	0.20±0.10	0.45±0.20	0.02Ω≤R<0.1Ω
0805	2.00 ±0.10	1.25±0.15	0.50±0.10	0.30 ±0.20	0.40 ±0.20	0.27±0.20	①0.65±0.20	①0.01Ω≤R<0.015Ω
							②0.55±0.20	②0.015Ω≤R<0.05Ω
							③0.65±0.20	③0.05 Ω≤R<0.1Ω
1206	3.20±0.20	1.60±0.15	0.55±0.10	0.50±0.20	0.50 ±0.20	0.32±0.20	①1.00±0.20	①0.01Ω≤R<0.05Ω
							②0.95±0.20	②0.05Ω≤R<0.1Ω
1210	3.20±0.20	2.50±0.20	0.55±0.10	0.50 ±0.20	0.50±0.20	0.33±0.20	①1.05±0.20	①0.01Ω≤R<0.05Ω
							②0.85±0.20	②0.05Ω≤R<0.1Ω
2010	5.00±0.20	2.50±0.20	0.55±0.10	0.60 ±0.20	0.60 ±0.20	0.40 ±0.20	①1.90±0.20	①0.01Ω≤R<0.05Ω
							②2.00±0.20	②0.05Ω≤R<0.1Ω
2512	6.30±0.20	3.20±0.20	0.55±0.10	0.60 ±0.20	0.60 ±0.20	0.50 ±0.20	①2.85±0.20	①0.01Ω≤R<0.015Ω
							②2.70±0.20	②0.015Ω≤R<0.05Ω
							③2.30±0.20	③0.05Ω≤R<0.1Ω
*2512	6.30 ±0.20	3.20±0.20	0.55±0.10	0.60±0.20	1.80 ±0.20	/	/	/
0508	1.25±0.10	2.00±0.15	0.55±0.10	0.30±0.20	0.30±0.20	0.30±0.20	0.30±0.20	0.01Ω≤R<0.1Ω
0612	1.60±0.20	3.20±0.15	0.55±0.10	0.30±0.20	0.35±0.20	0.35±0.20	0.30±0.20	0.01Ω≤R<0.1Ω
1225	3.20±0.20	6.40±0.20	0.55±0.10	0.40±0.20	0.75 ±0.20	0.75±0.20	0.40 ±0.20	0.01Ω≤R<0.1Ω
*1225	3.20±0.20	6.40±0.20	0.55±0.10	0.40±0.20	1.05 ±0.20	/	/	/

◆产品特性曲线图Product Characteristic Curve

*负荷下降曲线Derating Curve



注：当电阻使用的环境温度超过70℃时，其额定负荷（额定功率或额定电流）按上述曲线下降。

Note:For resistors operated in ambient over70℃,rated load(rated power or rated current)shall be derated in accordance with the above figure.

◆额定值 Ratings

型号 Type	阻值范围 Resistance Range	70℃下额定功率 Rated Powerat70℃(W)		
0402	$0.1\Omega \leq R < 1\Omega$	C:1/16	E:1/8	Y:1/6
0603	$0.02\Omega \leq R < 1\Omega$	D:1/10	Q:1/5	---
0805	$0.01\Omega \leq R < 1\Omega$	E:1/8	F:1/4	---
1206	$0.01\Omega \leq R < 1\Omega$	F:1/4	G:1/2	---
1210	$0.01\Omega \leq R < 1\Omega$	R:1/3	G:1/2	H:3/4
2010	$0.01\Omega \leq R < 1\Omega$	H:3/4	J:1	---
2512	$0.01\Omega \leq R < 1\Omega$	J:1	---	---
	$0.1\Omega \leq R < 1\Omega$	L:2	---	---
0508	$0.01\Omega \leq R < 1\Omega$	R:1/3	G:1/2	---
0612	$0.01\Omega \leq R < 1\Omega$	J:1	---	---
1225	$0.01\Omega \leq R < 1\Omega$	L:2	---	---
	$0.1\Omega \leq R < 1\Omega$	N:3	---	---
注 Note	1、 电流为直流或交流有效值。Current of DC or ACRMS value. 2、 $I = \sqrt{P/R}$ 或元件极限电流两者中的较小值。 $I = \sqrt{P/R}$ or Limiting element voltage whichever is lower. I: 额定电流Rated Current(A) P: 额定功率Rated power(W) R: 标称阻值Normal resistance(Ω)			

型号Type	阻值范围 Resistance Range			电阻温度系数 T.C.R(ppm/°C)	
	±1%	±3%	±5%	PPM/°C	代号Code
0402	$0.1\Omega \leq R < 0.5\Omega$			±500	M
	$0.5\Omega \leq R < 1\Omega$			±200	W
0603	$0.02\Omega \leq R < 0.05\Omega$			±800	Q
	$0.05\Omega \leq R < 0.1\Omega$			±300	B
	$0.1\Omega \leq R < 1\Omega$			±200	W
0805	$0.01\Omega \leq R < 0.015\Omega$			±1200	Z
	$0.015\Omega \leq R < 0.025\Omega$			±600	A
	$0.025\Omega \leq R < 0.05\Omega$			±400	U
	$0.05\Omega \leq R < 1\Omega$			±200	W
1206	$0.01\Omega \leq R < 0.02\Omega$			±800	Q
	$0.02\Omega \leq R < 0.05\Omega$			±500	M
	$0.05\Omega \leq R < 0.068\Omega$			±300	B
	$0.068\Omega \leq R < 1\Omega$			±200	W
1210	$0.01\Omega \leq R < 0.02\Omega$			±800	Q
	$0.02\Omega \leq R < 0.05\Omega$			±400	U
	$0.05\Omega \leq R < 1\Omega$			±200	W
2010	$0.01\Omega \leq R < 0.02\Omega$			±800	Q
	$0.02\Omega \leq R < 0.05\Omega$			±400	U
	$0.05\Omega \leq R < 1\Omega$			±200	W
2512	$0.01\Omega \leq R < 0.02\Omega$			±800	Q
	$0.02\Omega \leq R < 0.05\Omega$			±200	W
	$0.05\Omega \leq R < 1\Omega$			±200	W
0508	$0.01\Omega \leq R < 0.02\Omega$			±800	Q
	$0.02\Omega \leq R < 0.1\Omega$			±300	B
	$0.1\Omega \leq R < 1\Omega$			±200	W
0612	$0.01\Omega \leq R < 0.03\Omega$			±800	Q
	$0.03\Omega \leq R < 0.1\Omega$			±300	B
	$0.1\Omega \leq R < 1\Omega$			±200	W
1225	$0.01\Omega \leq R < 0.06\Omega$			±500	M
	$0.06\Omega \leq R < 0.25\Omega$			±200	W
	$0.25\Omega \leq R < 1\Omega$			±100	K

◆可靠性测试方法Reliability Test Method

项目 Item	标准 Specifications	测试方法 Test Methods
高温存储 High Temperature Exposure (Storage)	无可见损伤 No mechanical damage 1%: $\Delta R \leq \pm(1.0\%R + 0.5m\Omega)$ 2%、3%、5%: $\Delta R \leq \pm(2.0\%R + 0.5m\Omega)$	AEC-Q200 Test 3 /MIL-STD-202 Method108 1000小时 @ T=155℃, 不通电。 1000hours. @ T=155℃. Unpowered.

◆可靠性测试方法Reliability Test Method

(续上页 Continue)

项目 Item	标准 Specifications	测试方法 Test Methods
温度循环 Temperature Cycling	无可见损伤 No mechanical damage 1%: $\Delta R \leq \pm(0.5\%R + 0.5m\Omega)$ 2%、3%、5%: $\Delta R \leq \pm(1.0\%R + 0.5m\Omega)$	AEC-Q200 Test 4/JESD22 Method JA-104 -55℃(30分钟)~常温(≤ 1 分钟)~155℃(30分钟), 1000个循环。 -55℃(30min)~normal temperature(≤ 1 min)~155℃(30min),1000 cycles.
高温高湿 Biased Humidity	无可见损伤 No mechanical damage $\Delta R \leq \pm(3.0\%R + 0.5m\Omega)$	AEC-Q200 Test 7/ MIL-STD-202 Method103 温度: 85℃, 湿度85%RH的条件下施加10%额定功率, 放置1000小时。 85℃/85%RH,Apply10% of operating power for1000hours.
工作寿命 Operational Life	无可见损伤 No mechanical damage 1%: $\Delta R \leq \pm(1.0\%R + 0.5m\Omega)$ 3%、5%: $\Delta R \leq \pm(3.0\%R + 0.5m\Omega)$	AEC-Q200 Test 8/ MIL-STD-202 Method108 125℃ $\pm 2^\circ\text{C}$,1000小时, 36%额定功率通1.5小时/断0.5小时。 125℃ $\pm 2^\circ\text{C}$, 1000h, 36%of rated power for1.5hON/0.5hOFF.
耐溶剂性 Resistance to Solvents	标志清晰, 无可见损伤 Clearly marked, No mechanical damage	AEC-Q200 Test12/ MIL-STD-202Method 215 浸在三种溶剂3min后擦拭10次, 浸、刷共3回来, 用水洗清洗剂进行清洗, 并且室温下对整个表面进行通风干燥。 Immersed in three solvents after 3min immersion, brush wipe 10 times, a total of 3 times, washing with washing and cleaning agent, room temperature on the surface of the ventilation drying.
机械冲击 Mechanical Shock	无可见损伤 No mechanical damage $\Delta R \leq \pm(1.0\%R + 0.5m\Omega)$	AEC-Q200 Test 13/ MIL-STD-202Method213 正半弦波, 峰值加速度: 100g's, 脉冲持续时间: 6ms, 三轴六向各3次, 共18次。 Positive half wave, peak acceleration:100g,s,pulse duration: 6ms, three axis six to each 3 times,a total of 18 times.
振动 Vibration	无可见损伤 No mechanical damage $\Delta R \leq \pm(1.0\%R + 0.5m\Omega)$	AEC-Q200 Test 14/ MIL-STD-202Method204 频率: 10Hz~2000Hz,加速度: 5g's, 一个循环20min, X、Y、Z三个方向每个方向12个循环, 共36个循环。 Frequency:10Hz ~ 2000Hz, acceleration:5g,s, a loop 20min, X, Y, Z three directions, each direction 12 cycles,36 cycles.
耐焊接热 Resistance to Soldering Heat	无可见损伤 No mechanical damage $\Delta R \leq \pm(1.0\%R + 0.5m\Omega)$	AEC-Q200 Test 15/ MIL-STD-202Method210 270℃ $\pm 5^\circ\text{C}$ 锡槽, 保持10s ± 1 s。 Lead-free solder bath at 270℃ $\pm 5^\circ\text{C}$ for10s ± 1 s.
热冲击 Thermal Shock	无可见损伤 No mechanical damage $\Delta R \leq \pm(1.0\%R + 0.5m\Omega)$	AEC-Q200 Test 16/MIL-STD-202Method107 -55℃(15分钟)~常温(≤ 20 秒)~155℃(15分钟), 300个循环。 -55℃(15min)~normal temperature(≤ 20 s)~155℃(15min),300 cycles.
ESD静电放电 Electrostatic Discharge (ESD)	无可见损伤 No mechanical damage $\Delta R \leq \pm(3.0\%R + 0.5m\Omega)$	AEC-Q200 Test 17/AEC-Q200-002 人体模式, 两次放电, 正、负极性各1次。 Human body model, 1pos+1neg. discharges. 0402/0603: 1kV; 0508:1.5kV; 0805、0612、1225: 2kV ; 1206及以上: 3kV
可焊性 Solderability	无可见损伤 No mechanical damage 可焊面积 $\geq 95\%$ 95% CoverMin	AEC-Q200 Test 18/IEC 60115-1 4.17245℃ $\pm 5^\circ\text{C}$ 锡槽, 保持3s ± 0.3 s。 Lead-free solder bath at 245℃ $\pm 5^\circ\text{C}$ for3s ± 0.3 s.
电阻温度系数 T.C.R	在规定值内 Within specified T.C.R	AEC-Q200 Test 19/IEC 60115-14.8+20℃/- 55℃/+20℃/+125℃/+20℃
可燃性 Flammability	不完全燃尽, 薄垫纸应不被引燃, 松木板应不被烤焦炭化。 No ignition of the tissue paper or scorching or the pinewood board.	AEC-Q200 Test 20/UL-94 V-0或V-1可接受。不需要电气测试。 V-0 or V-1 are acceptable.Electrical test not required.


◆可靠性测试方法Reliability Test Method

(续上页 Continue)


项目 Item	标准 Specifications	测试方法 Test Methods
基板弯曲试验 Substrate Bending Test	无可见损伤 No mechanical damage 1%: $\Delta R \leq \pm(0.5\%R + 0.5m\Omega)$ 3%、5%: $\Delta R \leq \pm(1.0\%R + 0.5m\Omega)$	AEC-Q200 Test 21/AEC-Q200-005 弯曲距离(Bending distance): 0402、0603、0805: 5mm; 1206、1210:4mm; 2010、2512:2mm; 0508:3mm;0612:2mm;1225:1mm 保持时间(Duration): 60s \pm 5s
端子强度 Terminal Strength	无可见损伤 No mechanical damage 1%: $\Delta R \leq \pm(0.5\%R + 0.5m\Omega)$ 3%、5%: $\Delta R \leq \pm(1.0\%R + 0.5m\Omega)$	AEC-Q200 Test 22/AEC-Q200-0060402 施加力 : 5N, 保持60 \pm 1秒。 0603及以上施加力:17. 7N, 保持60 \pm 1秒。 For 0402:Applying force 5N for60s \pm 1s. For 0603and above size:Applying force17.7N for60s \pm 1s.
阻燃性 Flame Retardance	不可燃 No flame	AEC-Q200 Test 24/AEC-Q200-001 9Vdc到32Vdc (钳位电流高达500A)、增量为 1. 0Vdc 的电压。每种电压等级最少施加1小时。 Subjected to voltage from 9.0 to 32.0 VDC(current clamped up to 500A),and each voltagelevelshallbeincreasedin1.0 VDC for one hour minimum.
绝缘电阻 Insulation Resistance	1000M Ω Min	IEC 60115-1 12.1 在电极与基片间施加100V \pm 15V直流电压, 保持1分钟, 然后测绝缘电阻值。 ApplyDC100V \pm 15Vbetween substrate and terminationsfor1min, then checkinsulation resistance.
耐电压 Voltage Proof	无击穿或飞弧 No breakdown or flashover	IEC 60115-1 12.2 在电极与基片间以大约100V/s的速率施加有效值为最大过负荷电压的交流 电压, 保持60s \pm 5s。 Apply max. overload voltage of ACRMS at a rate of approximately100V/s between substrate and terminationsfor60s \pm 5s.
短时间过负载 Short Time Overload	无可见损伤 No mechanical damage 1%: $\Delta R \leq \pm(1.0\%R + 0.5m\Omega)$ 3%、5%: $\Delta R \leq \pm(2.0\%R + 0.5m\Omega)$	IEC 60115-1 8.1 2.5倍额定电流, 持续5秒。 2.5 times rated current for5s.
低温负载 Operation at Low Temperature	无可见损伤 No mechanical damage 1%: $\Delta R \leq \pm(1.0\%R + 0.5m\Omega)$ 3%、5%: $\Delta R \leq \pm(2.0\%R + 0.5m\Omega)$	IEC 60115-1 10.2 -55 $^{\circ}$ C \pm 5 $^{\circ}$ C, 无负载1小时, 额定电流45分钟, 无负载15分钟。 -55 $^{\circ}$ C \pm 5 $^{\circ}$ C, 1h without load, rated current for 45min,15min withoutload.
抗硫化性能 Sulfuration Resistant	无可见损伤 No mechanical damage $\Delta R \leq \pm(5.0\%R + 0.5m\Omega)$	方法一 Method one: 预处理: 3次回流焊+100次温度循环 Pretreatment:three times reflow soldering+100times temperature shock. 油浴, 恒温: 105 $^{\circ}$ C \pm 3 $^{\circ}$ C, 放置时间: 1000小时 Soaked in industrial oil with sulfur substancecontainedin105 $^{\circ}$ C \pm 3 $^{\circ}$ C for1000h.
	无可见损伤 No mechanical damage $\Delta R \leq \pm(1.0\%R + 0.5m\Omega)$	方法二 Method two: ASTM-B-809-95: 把待测电阻放置在饱和硫蒸气内, 温度: 60 $^{\circ}$ C \pm 3 $^{\circ}$ C, 湿度: 91%RH ~93%RH, 放置时间: 1500小时。 ASTM-B-809-95: Place the resistor to be measured in saturated sulfur vapor, Temperature:60 $^{\circ}$ C \pm 3 $^{\circ}$ C ,humidity:91%RH ~93%RH, 1500hours.
	无可见损伤 No mechanical damage $\Delta R \leq \pm(1.0\%R + 0.5m\Omega)$	方法三 Method three: EIA-977 硫磺熏蒸, 恒温: 105 $^{\circ}$ C \pm 3 $^{\circ}$ C, 放置时间: 1500小时。 Sulfur fumigation, constant temperature: 105 $^{\circ}$ C \pm 3 $^{\circ}$ C for 1500 hours.

◆阻值标准测量位置 Standard Measuring Position for Resistance Value

For $R < 100\text{m}\Omega$:




For $R > 100\text{m}\Omega$:



◆推荐焊盘尺寸 Recommend Solder Pad Size

单位 unit: mm



型号 Type	阻值 (mΩ)	A	B	C
0402	100~999	0.45	1.45	0.60
0603	20~999	0.80	2.50	0.95
0805	10~99.9	0.55	3.25	1.40
	100~999	1.05		
1206	10~99.9	1.30	4.50	1.75
	100~999	1.90		
1210	10~49.9	1.20	4.60	2.70
	50~99.9	1.60		
	100~999	2.00		
2010	10~99.9	1.20	6.50	2.70
	100~999	3.50		
2512	10~14.9	0.90	7.80	3.40
	15~50	1.20		
	50~99.9	2.00		
	100~999	4.80		
2512 (2W)	100~999	2.60	7.80	3.40
0508	10~999	0.60	2.20	2.00
0612	10~999	0.60	2.90	3.30
1225	10~999	1.40	4.50	6.40

注：电阻焊接后，电阻值可能因焊盘面积、焊盘间距、焊锡量的差别而发生变化。顾客在设计电路及选型时，必须充分而全面的考虑及评判适用性。

After soldering, the resistance value may change due to the difference of pad area, pads pacing and solder quantity. When designing circuits and selecting models, customers must comprehensively consider and evaluate the applicability.


◆包装 Packaging

包装方式见附录 Packaging can refer to the Appendix.

附录 Appendix I


◆推荐焊盘尺寸 Recommend Solder Pad Size

* 片式固定电阻器 Chip fixed resistor 单位 unit: mm



厚膜电阻及薄膜电阻 Thick Film Resistor and Thin Film Resistor			
型号 Type	A	B	C
01005	0.17±0.03	0.60±0.03	0.22±0.03
0201	0.23±0.05	0.84±0.05	0.38±0.05
0402	0.45±0.05	1.45±0.05	0.60±0.05
0603	0.80±0.05	2.50±0.05	0.95±0.05
0805	1.05±0.1	3.25±0.1	1.40±0.1
1206	1.90±0.1	4.50±0.1	1.75±0.1
1210	2.00±0.1	4.60±0.1	2.70±0.1
2010	3.50±0.1	6.50±0.1	2.70±0.1
2512(1W、1.5W)	4.80±0.1	7.80±0.1	3.40±0.1
2512(2W)	2.70±0.1	7.80±0.1	3.60±0.1
0508	0.60±0.1	2.20±0.1	2.00±0.1
0612	0.60±0.1	2.90±0.1	3.30±0.1
1225	1.40±0.1	4.50±0.1	6.40±0.1

* 厚膜片式网络电阻器 Thick film chip network resistor



单位 unit: mm


型号 Type	A	B	Q1	Q2	Q3
2R01	0.30±0.05	0.90±0.05	0.30±0.05	0.20±0.05	---
4R01	0.30±0.05	0.90±0.05	0.20±0.05	0.20±0.05	0.20±0.05
2R02	0.35±0.05	1.25±0.05	0.65±0.05	0.20±0.05	0.30±0.05
4R02	0.38±0.05	1.60±0.05	0.40±0.05	0.20±0.05	---
4R03	0.80±0.05	2.70±0.05	0.60±0.05	0.40±0.05	0.40±0.05
备注 Remarks	1、2R01型号包含including:RC-MY04、RCMY04、RH-MY04、RHMY04 2、4R01型号包含including:RC-MY08、RCMY08、RH-MY08、RHMY08 3、2R02型号包含including:RC-MT04、RCMT04、RH-MT04、RHMT04 4、4R02型号包含including:RC-MT08、RCMT08、RH-MT08、RHMT08 5、4R03型号包含including:RC-ML08、RCML08、RH-ML08、RHML08 6、上述型号说明适用于附录中所有型号。 The above description applies to all types in the appendix.				

◆包装 Packaging

* 纸带编带 Paper Taping

适用于01005、0201、0402、2R01、4R01、2R02、4R02:

For 01005、0201、0402、2R01、4R01、2R02、4R02:



单位unit: mm


型号Type	A	B	W	F	E
01005	0.45±0.02	0.25±0.02	8.00±0.02	3.50±0.05	1.75±0.05
0201	0.70±0.10	0.40±0.10	8.00±0.20	3.50±0.05	1.75±0.10
0402	1.15±0.10	0.65±0.10	8.00±0.20	3.50±0.05	1.75±0.10
2R01	0.97±0.05	0.77±0.05	8.00±0.20	3.50±0.05	1.75±0.10
4R01	1.57±0.05	0.77±0.05	8.00±0.20	3.50±0.05	1.75±0.10
2R02	1.45±0.10	1.20±0.10	8.00±0.20	3.50±0.05	1.75±0.10
4R02	2.20±0.10	1.20±0.10	8.00±0.20	3.50±0.05	1.75±0.10

单位unit: mm

型号Type	P	P0	P1	ΦD0	T1	T
01005	2.00±0.05	4.00±0.10	2.00±0.05	1.55±0.02	0.17±0.02	0.31±0.02
0201	2.00±0.05	4.00±0.10	2.00±0.05	1.50±0.10	0.28±0.04	0.42±0.05
0402	2.00±0.05	4.00±0.10	2.00±0.05	1.50±0.10	/	0.44±0.05
2R01	2.00±0.10	4.00±0.10	2.00±0.05	1.50±0.10	/	0.60±0.10
4R01	2.00±0.10	4.00±0.10	2.00±0.05	1.50±0.10	/	0.60±0.10
2R02	2.00±0.10	4.00±0.10	2.00±0.05	1.50±0.10	/	0.60±0.10
4R02	2.00±0.10	4.00±0.10	2.00±0.05	1.50±0.10	/	0.60±0.10

适用于0603、0805、0508、1206、0612、1210、4R03:

For 0603、0805、0508、1206、0612、1210、4R03:



单位unit: mm

型号Type	A	B	W	F	E
0603	1.80±0.10	1.05±0.10	8.00±0.20	3.50±0.05	1.75±0.10
0805	2.30±0.10	1.50±0.10	8.00±0.20	3.50±0.05	1.75±0.10
0508	2.30±0.10	1.50±0.10	8.00±0.20	3.50±0.05	1.75±0.10
1206	3.50±0.20	1.90±0.20	8.00±0.20	3.50±0.05	1.75±0.10
0612	3.50±0.20	1.90±0.20	8.00±0.20	3.50±0.05	1.75±0.10
1210	3.50±0.20	2.80±0.20	8.00±0.20	3.50±0.05	1.75±0.10
4R03	3.50±0.20	1.90±0.20	8.00±0.20	3.50±0.05	1.75±0.10


单位unit: mm

型号Type	P	P0	P1	ΦD0	T	
					厚膜电阻及薄膜电阻 Thick Film Resistor and Thin Film Resistor	合金片式固定电 阻 Metal Foil resistor
0603	4.00±0.10	4.00±0.10	2.00±0.05	1.50±0.10	0.60±0.10	0.75±0.10
0805	4.00±0.10	4.00±0.10	2.00±0.05	1.50±0.10	0.75±0.10	0.95±0.10
0508	4.00±0.10	4.00±0.10	2.00±0.05	1.50±0.10	0.75±0.10	0.95±0.10
1206	4.00±0.10	4.00±0.10	2.00±0.05	1.50±0.10	0.75±0.10	0.95±0.10
0612	4.00±0.10	4.00±0.10	2.00±0.05	1.50±0.10	0.75±0.10	0.95±0.10
1210	4.00±0.10	4.00±0.10	2.00±0.05	1.50±0.10	0.75±0.10	---
4R03	4.00±0.10	4.00±0.10	2.00±0.05	1.50±0.10	0.75±0.10	---

***塑料带编带 Embossed Taping**

适用于2010、2512、1225:

For 2010、2512、1225:




单位unit: mm

型号Type	A0	B0	W	F	E	t
2010	5.50±0.15	2.82±0.15	12.00±0.10	5.50±0.10	1.75±0.10	0.25±0.05
2512	6.78±0.15	3.45±0.15	12.00±0.10	5.50±0.10	1.75±0.10	0.25±0.05
1225	6.78±0.15	3.45±0.15	12.00±0.10	5.50±0.10	1.75±0.10	0.25±0.05

单位unit: mm

型号Type	P	P0	P1	ΦD0	ΦD1	K0	
						厚膜电阻及薄膜电阻 Thick Film Resistor and Thin Film Resistor	合金片式固定电阻 Metal Foil resistor
2010	4.00±0.10	4.00±0.10	2.00±0.05	1.50+0.10/-0	1.50±0.10	0.84±0.10	0.84±0.10
2512	4.00±0.10	4.00±0.10	2.00±0.05	1.50+0.10/-0	1.50±0.10	0.81±0.10	1.00±0.10
1225	4.00±0.10	4.00±0.10	2.00±0.05	1.50+0.10/-0	1.50±0.10	0.81±0.10	1.00±0.10

* 卷盘 Reel



单位unit: mm

卷盘尺寸 Reel Type	型号Type	M	W	T	A	B	C	D
7英寸 7inch dia.Reel	01005、0201 0402、0603 0805、1206 1210、2R01 4R01、2R02 4R02、4R03 0508、0612	178±2.0	9.5±1.0	12.5±1.5	2.0±0.5	13.0±0.5	21.0±0.5	58.0±2.0
	2010、2512	178±2.0	13.0±0.5	15.5±1.5	2.0±0.5	13.0±0.5	21.0±0.5	57.0±2.0
	1225	178±2.0	13.0±0.5	15.5±1.5	2.0±0.5	13.0±0.5	21.0±0.5	57.0±2.0
13英寸 13 inch dia.Reel	0201、0402 0603、0805 1206	330±2.0	9.5±1.0	13.4±1.0	2.0±0.5	13.0±0.5	21.0±0.5	100.0±1.0

◆ 编带包装能力 Taping Ability


面带拉力 Top tape peel strength

面带拉力强度未11g~70g (0.1N~0.7N) , 速度: 300mm/min, 经下列试验后不允许有破裂断带现象。

Peel strength is 11g~70g (0.1N~0.7N),with speed of 300mm/min,and should not have flash and

tear after peeling.

测试方法 Test method:



电阻松动自如，无粘面胶带、底胶带现象。

Resistor is free, no sticking to top tape and bottom tape.

电阻易从纸带中取出，且晶片孔无机械损伤。

Resistor is easy to take out from carrier tape and chip hole have no mechanical damage.

◆包装数量 Packaging Quantity

包装方法 Packaging style	7英寸 7inch dia.Reel					13英寸 13 inch dia.Reel	
型号 Type	01005	0201	0402、2R01 2R02、4R01 4R02	0603、0805 1206、1210 4R03、0508 0612	2010、2512 、1225	0201、 0402	0603、0805、 1206
数量 Quantity (pcs)	20000	15000	10000	5000	4000	50000	20000

◆IEC E-24、E-96系列电阻值代码对照表 IEC E-24、E-96 Series Resistance Cross-reference List

* E-24 系列 E-24 series ($\times 10^n \Omega$)

(单位 unit: 0.001 Ω 、0.01 Ω 、0.1 Ω 、1 Ω 、10 Ω 、100 Ω 、1k Ω 、10k Ω 、100k Ω 、1M Ω 、10M Ω 、100M Ω 、1000M Ω)

表一 Table One:

1.0	1.5	2.2	3.3	4.7	6.8
1.1	1.6	2.4	3.6	5.1	7.5
1.2	1.8	2.7	3.9	5.6	8.2
1.3	2.0	3.0	4.3	6.2	9.1

* E-96系列 E-96 series ($\times 10^n \Omega$)

(单位 unit: 0.001 Ω 、0.01 Ω 、0.1 Ω 、1 Ω 、10 Ω 、100 Ω 、1k Ω 、10k Ω 、100k Ω 、1M Ω 、10M Ω 、100M Ω 、1000M Ω)

表二 Table Two:

1.00	1.33	1.78	2.37	3.16	4.22	5.62	7.50
1.02	1.37	1.82	2.43	3.24	4.32	5.76	7.68
1.05	1.40	1.87	2.49	3.32	4.42	5.90	7.87
1.07	1.43	1.91	2.55	3.40	4.53	6.04	8.06
1.10	1.47	1.96	2.61	3.48	4.64	6.19	8.25
1.13	1.50	2.00	2.67	3.57	4.75	6.34	8.45
1.15	1.54	2.05	2.74	3.65	4.87	6.49	8.66
1.18	1.58	2.10	2.80	3.74	4.99	6.65	8.87
1.21	1.62	2.15	2.87	3.83	5.11	6.81	9.09
1.24	1.65	2.21	2.94	3.92	5.23	6.98	9.31
1.27	1.69	2.26	3.01	4.02	5.36	7.15	9.53
1.30	1.74	2.32	3.09	4.12	5.49	7.32	9.76

* E-96系列0603型号《乘数代码对照表》及《电阻值代码对照表》

E-96 series(0603)《multiplied Cross-reference List》And《Resistance Cross-reference List》

表三 Table Three:

乘数multiplied	$\times 10^0$	$\times 10^1$	$\times 10^2$	$\times 10^3$	$\times 10^4$	$\times 10^5$	$\times 10^6$	$\times 10^7$	$\times 10^{-1}$	$\times 10^{-2}$	$\times 10^{-2}$	$\times 10^{-3}$
代码code	A	B	C	D	E	F	G	H	X	Y	Y	Z

表四 Table Four:

代号 code	E-96系列电阻 E-96 resistance	代号 code	E-96系列电阻 E-96 resistance	代号 code	E-96系列电阻 E-96 resistance	代号 code	E-96系列电阻 E-96 resistance
01	100	25	178	49	316	73	562
02	102	26	182	50	324	74	576
03	105	27	187	51	332	75	590
04	107	28	191	52	340	76	604
05	110	29	196	53	348	77	619
06	113	30	200	54	357	78	634
07	115	31	205	55	365	79	649
08	118	32	210	56	374	80	665
09	121	33	215	57	383	81	681
10	124	34	221	58	392	82	698
11	127	35	226	59	402	83	715
12	130	36	232	60	412	84	732
13	133	37	237	61	422	85	750
14	137	38	243	62	432	86	768
15	140	39	249	63	442	87	787
16	143	40	255	64	453	88	806
17	147	41	261	65	464	89	825
18	150	42	267	66	475	90	845
19	154	43	274	67	487	91	866
20	158	44	280	68	499	92	887
21	162	45	287	69	511	93	909
22	165	46	294	70	523	94	931
23	169	47	301	71	536	95	953
24	174	48	309	72	549	96	976

◆厚膜电阻阻值代码及标记规则

Description for Resistance Value Code and Marking of Thick Film Chip Resistor

* 阻值代码 Resistance Value Code

所有厚膜电阻的阻值代码与其标记是相对的。

All the resistance value code of thick film chip resistor is corresponding with the marking.

* 标记 Marking

* E-24系列（0603、 $\geq \pm 5\%$ ）：采用三位数字表示，前二位表示电阻值有效数字，第三位表示乘以10的次方数。

E-24 series: Express resistance value on the glass side with three digits, the first two digits should be significant and the third one denotes number of zeros.

例For example



30K Ω



33 Ω

*E-24系列 (0603、 $\leq \pm 1\%$)：在三位数字标记下方增加下横线识别。

E-24 series (0603、 $\leq \pm 1\%$): One short bar under marking letter.

例 For example:




*E-96系列和E-24系列 (0508、0805、0612、1206、1225、1210、2010、2512、 $\pm 1\%$ & $\pm 0.5\%$)：

▲采用四位数字表示，前三位表示电阻值有效数字，第四位表示乘以10的次方数。

E-96 series & E-24 series (0508、0805、0612、1206、1225、1210、2010、2512、 $\pm 1\%$ & $\pm 0.5\%$): Express the resistance value with four digits, the first three digits are significant figures and the fourth de notes the number of zeros.

例 For example:




*E-96系列 (0603、 $\leq \pm 1\%$)：

▲采用三位代码表示，前两位表示E-96系列阻值代码，后一位字母表示乘数代码（见表三和表四）。

Express the resistance value with three code, the first two digit code denote the resistance of E-96 series, and the third code of letter denote the multiplier (see the table three and four).

例 For example:



*小数点以“R”表示 The decimal point should be expressed by “R” .

例 For example:



*跨接电阻以“0”表示 The jumper should be expressed by “0”

例 For example:



* ≤ 0402 产品不作标记：For the chip resistor (≤ 0402) , there is no mark on the glass side.

例 For example:



*非IEC标准系列的电阻值标记表示方法：一般以最接近IEC E24系列标称阻值的标记表示方法。

For the resistance values which don't belong to IEC serial, use the resistance of IEC serial which is most close to the required resistance of non-IEC serial for replacement.

*客户对标记有特殊要求时，则按照协商的结果印刷标记。

To get agreement by both party if the customers have special requirements for the marking.

◆薄膜电阻阻值代码及标记规则

Description for Resistance Value Code and Marking of Thin of Thin Film Chip Resistor

* 阻值代码 Resistance Value Code

所有薄膜电阻全尺寸统一采用四位数阻值代码表示。

All resistance value code of thin film chip resistor used four digits.

例Example

TD03G4701BT

四位数代号表示，如：4701=4.7K Ω ；1R50=1.5 Ω

To use four digits codes represent resistance value,

例Example 4701=4.7K Ω 1R50=1.5 Ω

* 标记 Marking

*当阻值同时存在于E24和E96系列时，优先采用E96系列。

When resistance value belongs to E24 as well as E96 series, we suggest preferentially use E96 series.

例Example 10K=1002, \neq 103

* \geq 0805产品标记For the chip resistor (\geq 0805) :

▲采用四位数字表示，前三位表示电阻值有效数字，第四位表示10的次方数。

Express the resistance value with four digits, the first three digits are significant figures and the fourth denotes the number of zeros.

例Example




*0603标记 Marking for 0603 Size Resistor

▲0603-E96系列：采用三位代码表示，前二位表示E-96系列阻值代码，后一位字母表示乘数代码（见表三和表四）；

Express the resistance value with three code, the first two digit code denote the resistance of E-

96 series, and the third code of letter denote the multiplier (see the table three and four).


例Example



▲0603-E24系列：采用三位数字表示，前二位表示电阻值有效数字，第三位表示10的次方数。


Express the resistance value on the glass side with three digits, the first two digits should be significant and the third denote number of zeros.

例Example



*▲小数点以“R”表示 The decimal point should be expressed by“R”.

例Example



* \leq 0402 产品：不作标记 For the chip resistor (\leq 0402), there is no mark on the glass side.

例Example



◆电流检测电阻阻值代码及标记规则

Description for resistance Value Code and Marking of Current Sensing Thick Film Chip Resistor

* 阻值代码 Resistance Value Code

所有电流检测电阻全尺寸统一采用四位数阻值代码表示。

All resistance value code of current sensing thick film chip resistor used four digits.

例Example

RBF03MR010FT

____ 四位数代号表示，如：R010=10mΩ；30M1=30.1mΩ

To use four digits codes represent resistance value,

例Example R010=10mΩ；30M1=30.1mΩ

* 标记 Marking

*E-24和E-96系列（0508、0805、0612、1206、1225、1210、2010、2512， $\leq \pm 5\%$ ）：采用四位标记代码。

For（0508、0805、0612、1206、1225、1210、2010、2512， $\leq \pm 5\%$ ），when resistance value belongs to E24 and E96 series, we suggest preferentially use four digits.

标记代码 Mark Code	阻值范围 Resistance Value	示例 Sample
R00×	1mΩ \leq R \leq 9mΩ	R005=5mΩ
R0×	10mΩ \leq R \leq 99mΩ	R033=33mΩ
R×	100mΩ \leq R \leq 999mΩ	R100=100mΩ
×	1mΩ<R<10mΩ（包含小数点后两位有效数字） (Contains two significant digits after the decimal point.)	5M10=5.1mΩ
×	10mΩ<R<100mΩ（包含小数点后一位数字） (Contains one significant digit after the decimal point.)	30M1=30.1mΩ

*E-24和E-96系列（0603， $\leq \pm 5\%$ ）：采用三位标记代码。

For the chip resistor (0603, $\leq \pm 5\%$), when resistance value belongs to E024 and E96 series, we suggest preferentially use three digits.

标记代码 Mark Code	阻值范围 Resistance Value	示例 Sample
V0×	1mΩ \leq R \leq 9mΩ	V05=5mΩ
V×	10mΩ \leq R \leq 99mΩ	V33=33mΩ
R×	100mΩ \leq R \leq 999mΩ	R100=100mΩ
×	1mΩ<R<10mΩ（包含小数点后一位有效数字） (Contains one significant digit after the decimal point.)	5M10=5.1mΩ

* ≤ 0402 产品不印刷标记。

For the chip resistor（ ≤ 0402 ），there is no mark on the glass side.

*非IEC标准系列的电阻标记表示方法：一般以最接近IEC E24系列标称阻值的标记表示方法。

For the resistance values which don't belong to IEC serial, use the resistance of IEC serial which is most close to the required resistance of non-IEC serial for replacement.

*客户对标记有特殊要求时，则按照协商的结果印刷标记。

To get agreement by both party if there special requirement for the marking.

◆片式电阻器使用说明 Chip Resistor Instructions For Use

* 本产品在以下特殊环境下应用，性能可能会受到影响：

- 1、在各种类型的液体，包括水、油、化学品、有机溶剂的使用。
- 2、在户外直接暴露在阳光的地方，或在灰尘多的地方使用。
- 3、在产品暴露的地方，有海风或腐蚀性气体，包括氯气、硫化氢、氨气、二氧化硫、二氧化氮。
- 4、在产品暴露于静电或电磁波的地方使用。
- 5、在产生热量的部件、塑料线，或其他易燃物品附近使用。
- 6、在用树脂或其他涂层材料密封产品的情况下使用。
- 7、焊接后使用不洁焊料或使用水或水溶性清洗剂清洗产品。
- 8、片状电阻器的基材是氧化铝。由于和安装基板的热膨胀系数不同，在反复施加提供热循环等热应力时，接合部的焊锡（焊锡部）有时会发生裂纹。如果环境温度反复发生很大的变动，并且载荷反复进行ON/OFF，则需要注意龟裂的发生。因热应力而发生的龟裂，取决于所安装的焊盘的大小、焊锡量、安装基板的散热性等，因此在环境温度有很大的变化或者载荷NO/OFF的条件下使用时，请充分注意以进行设计。

* Application of the products in a special environment can deteriorate product performance:

- 1、Use in various types of liquid, including water, oils, chemicals, and organic solvents.
- 2、Use outdoors where the products are exposed to direct sunlight, or in dusty places.
- 3、Use in places where the products are exposed to sea winds or corrosive gases, including Cl₂, H₂S, NH₃, SO₂, and NO₂ etc.
- 4、Use in places where the products are exposed to static electricity or electromagnetic waves.
- 5、Use in proximity to heat-producing components, plastic cords, or other flammable items.
- 6、Use involving sealing or coating the products with resin or other coating materials.
- 7、Use involving unclean solder or use of water or water-soluble cleaning agents for cleaning after soldering.
- 8、The substrate of chip resistors is alumina. Cracks may occur at the connection of solder (solder fillet portion) due to the difference of the coefficient of thermal expansion from a mounting board when heat stresses like heat cycle, etc. are repeatedly given to them. Care should be taken to the occurrence of the cracks when the change in ambient temperature or ON/OFF of load is repeated. The occurrence of the crack by heat stress may be influenced by the size of a pad, solder volume, heat radiation of mounting board etc., so please pay careful attention to designing when a big change in ambient temperature and conditions for use like ON/OFF of load can be assumed.

◆储存方法 Storage Conditions

温度5℃~30℃，相对湿度30%RH~70%RH。建议在符合上述储存条件下十二个月内使用。

T: 5℃~30℃, RH: 30%RH~70%RH. The products are suggested to be used within twelve months when received, and the storage condition mentioned above should be followed.

◆产品使用注意事项

- 1、避免采用超过正常额定功率的功率，超过额定功率的稳态负载条件下可能会对产品性能和可靠性产生负面影响。
- 2、用镊子拿起产品时要小心，有可能会将保护或电阻体夹碎。
- 3、手动安装产品时，烙铁头勿触碰产品。
- 4、用于车载设备、医疗设备、航空设备以及其他涉及人身安全、或可能引起重大损失的设备上时，请务必事先与我公司联系。这些产品在这类用途中出现故障或失灵可能导致人身事故或严重损坏。

◆Precautions on use of products


- 1、Avoid applying power exceeding normal rated power, exceeding the power rating under steady-state loading condition may negatively affect product performance and reliability.
- 2、Be careful when pick up the products with tweezers. There may be a care that the overcoat and / or the body can be chipped.

- 3、Soldering tip shall not touch the product when install product manually.
- 4、Contact our sales representatives before you use our products for applications including automotive, medical equipment and aerospace equipment. Malfunction or failure of the products in such applications may cause loss of human life or serious damage.

◆焊接Soldering

- 回流焊要求：器件回流焊要求满足J-STD-020无铅回流焊，具体要求如下：

Reflow soldering requirements: The device reflow soldering requirements meet the J-STD-020 lead-free reflow soldering. The specific requirements are as follows:




*降温速率 (Ramp-up rate(TP-TL)) : $\leq 6 / s^{\circ}C$

*预热温度 (Preheat/soak) : $150^{\circ}C - 200^{\circ}C$ (TSmin to TSmax) : 60-120s

液相线 $217^{\circ}C$ 以上时间 Time above $217^{\circ}C$ of liquid phase (TL) : 60-150s.

- 波峰焊的要求 Requirements for wave welding



*预热温度要求时间 Preheating temperature requirement: 130 -160 time: 60-90s

*插装元器件引脚在 $260^{\circ}C$ 焊料槽中至少停留10s (Sn93.5-Ag3.0-Cu0.5)

The pins of the plug-in components stay in the 260 solder channel for 10s.

- * 推荐的焊膏类型 Recommended solder alloy: 96.5Sn-3.0Ag-0.5Cu

◆修订履历Revision History

版本 Version	日期 Date	修订内容 Change Description	修订确认 Checked by
I 7.0	2026-01-04	-新增硫化试验测试方法 Add test method of sulfuration-resistant test. -附录：修改回流焊曲线和波峰焊曲线。 Appendix:Modify the requirements for the reflow soldering profile and the wave solder profile.	唐文宣 WenXuan Tang
I 6.0	2025-10-24	-修改可靠性测试方法部分试验方法的引用条款。 Modify the reference clauses of test methods in the section on reliability test methods. -电性能参数：修改0402规格 $0.1\Omega \leq R < 0.5\Omega$ 阻值段的TCR标准。 Electrical Performance Parameters : Modify the TCR standard for the 0402 package with resistance range of $0.1\Omega \leq R < 0.5\Omega$	唐文宣 WenXuan Tang
V5.0	2025-09-04	-附录：修改储存方法。 - Appendix: Modify the storage conditions.	刘瀚阳 Hanyang Liu
V 4.0	2024-09-13	-新增 0508 尺寸产品相关参数。 Add the parameters of 0508 type chip resistor.	肖洪立 Hongli Xiao
V 3.0	2023-12-18	-修改“规格尺寸”。Torevise the dimensions. -修改“额定值”格式。Revise the format of Ratings. 特性:修改工作寿命、短时间过负载、高温高湿、低温负载试验项目的测试方法。 Characteristics: to revise the test method of the operation life,short time overload,biased humidity,operation at low temperature test items. 特点:增加潮敏等级 MSL1Features:add the MSL 1 品名构成:增加 13 寸卷盘代号, 删除+2%、+10%、+20%精度 Part number: add 13inch reel code,delete tolerance of +2%、+10%、+20% 附录:增加 13 寸卷盘编带尺寸;增加 0508、0612、1225 包装、阻值代码及标记规则。 Appendix: add the dimentions of 13 inch reel: Add the parameters of 0508、0612、1225.	方敏 Min Fang 卢振强 ZhengiangLu
V 2.0	2023-09-07	特性:修改“抗硫化性能”试验放置时间由 500 小时修改为 1000 小时。 Characteristics:revise the test time of sulferation resistance from 500 hours to 1000hours	方敏 Min Fang
V 1.0	2023-07-26	-原版 The original version.	王跃伟 Yuewei Wang

注:上述所提供之内容为产品规格说明。在产品未变更时, 风华保有修改此内容不另行通知之所有权利, 任何产品变更将会以PCN通知客户。
 Remark:Information provided above is intended to indicate product specifications only. Fenghua reserves all the rights for revising this content without further notification, as long as products are unchanged. Any product change will be announced by PCN.